

127 OLIVE LACE UP MID CUT SAFETY BOOT
SIZE: UK 4 - 11

LABELLING ACCORDING TO STANDARD

 STANDARD FOR
 SAFETY
 FOOTWEAR MS
 ISO 20345:2008

RATED: S1

ADDITIONAL

P: PUNCTURE RESISTANT MIDSOLE

MATERIAL DESCRIPTION

UPPER

ECO LEATHER

 COLLAR &
 TONGUE

HIGH ABRASION MESH NYLON FABRIC

LINING

BREATHABLE WATERPROOF MAMBRANE LINING

VAMP LINING

BREATHABLE WATERPROOF MAMBRANE LINING

THREAD

ANTIWICK BONDED NYLON

EYELET

NYLON PLASTIC EYELET + NYLON STRIP



COUNTER	THERMOPLASTIC 1.1 – 1.3mm
FOOTBED	FULL PADDED
OUTSOLE	DUAL DENSITY DIRECT INJECTION POLYURETHANE + NON-MARKING NITRILE RUBBER (NBR)
TOE CAP	COMPOSITE TOE CAP COMPLY TO EN12568
NAIL PENETRATION	ANTI PERFORATION FABRIC MID-SOLE EN 12568 NAIL PENETRATION RESISTANT 1100N
SHOE LACE	POLYESTER SHOE LACE
PACKING	CORRUFATED PRINTED BOX

ADDITIONAL FEATURES

ESD	Excellent discharge capability, the shoe is suitable for work in ESD sensitive or electrostatically protected areas (EPA). The shoes comply to the standard 61340-5-1. ESD specification with bleeder resistor below 35 megaohms.
-----	---

ICON DESCRIPTION

	TOE IMPACT RESISTANT 200J
	TOE COMPRESSION RESISTANT 20,000 NEWTON
	PUNCTURE RESISTANT 1,100 NEWTON
	ECO LEATHER
	HYDROCARBON OUTSOLE FUEL & OIL RESISTANT VOLUME INCREASE ≤ 12%

	HEAT RESISTANCE OUTSOLE (HRO) OUTSOLE HEAT CONTACT RESISTANCE 300°C FOR 1 MIN
	VAPOR PERMEABILITY WATER VAPOUR PERMEABILITY: $\geq 0.8\text{mg/cm}^2$ WATER VAPOUR COEFFICIENT: $\geq 15\text{mg/cm}^2$
	ERGONOMICS COMFORTABLE FITTING & STABILITY SUPPORT
	Broad Fitting Reduce Exacerbate on Toe & Bunion
	SLIP RESISTANCE (FORWARD DIRECTION) ≥ 0.31 (CERAMIC & CLEANER) ≥ 0.19 (CERAMIC & GLYCERIN)
	SLIP RESISTANCE (BACKWARD DIRECTION) ≥ 0.36 (CERAMIC & CLEANER) ≥ 0.22 (CERAMIC & GLYCERIN)
	Shock Absorption Heel Region Energy Absorption
	Metal Free Non-Metallic Footwear
	Electrostatic Discharge (ESD)