

.1901 MAROON BROWN LOW CUT LACE SAFETY SHOE

SIZE: UK 4 - 10



LABELLING ACCORDING TO STANDARD

STANDARD FOR SAFETY FOOTWEAR MS ISO 20345:2008	RATED: SB
ADDITIONAL	P: PUNCTURE RESISTANT MIDSOLE


MATERIAL DESCRIPTION

UPPER	COW FULL GRAIN - THICKNESS: 2.0 - 2.2 mm
COLLAR & TONGUE	COW FULL GRAIN - THICKNESS: 2.0 - 2.2 mm
LINING	BEIGE AIRMESH LINING 300GSM
VAMP LINING	NON-WOVEN FABRIC LINING
THREAD	ANTIWICK BONDED NYLON
EYELET	NYLON PLASTIC EYELET
COUNTER	THERMOPLASTIC 1.1 – 1.3mm

FOOTBED	FULL PADDED
OUTSOLE	WALL STITCHED CEMENTED NON MARKING NITRILE RUBBER (NBR)
TOE CAP	STEEL TOE CAP COMPLY TO EN12568
NAIL PENETRATION	ANTI PERFORATION FABRIC MID-SOLE EN 12568 NAIL PENETRATION RESISTANT 1100N
SHOE LACE	POLYESTER SHOE LACE
PACKING	CORRUFATED PRINTED BOX

ADDITIONAL FEATURES

ESD	N/A
-----	-----

ICON DESCRIPTION	
	TOE IMPACT RESISTANT 200J
	TOE COMPRESSION RESISTANT 20,000 NEWTON
	PUNCTURE RESISTANT 1,100 NEWTON
	GENUINE LEATHER
	HYDROCARBON OUTSOLE FUEL & OIL RESISTANT VOLUME INCREASE $\leq 12\%$
	HEAT RESISTANCE OUTSOLE (HRO) OUTSOLE HEAT CONTACT RESISTANCE 300°C FOR 1 MIN
	VAPOR PERMEABILITY WATER VAPOUR PERMEABILITY: $\geq 0.8\text{mg/cm}^2$ WATER VAPOUR COEFFICIENT: $\geq 15\text{mg/cm}^2$
	Ergonomics Comfortable Fitting & stability Support