



SAFETY JOGGER

INDUSTRIAL



Light

FREEDOM S1PS LOW

FYTS1PSL

Lightweight Safety Shoes With Extra-Wide Toe

Free your toes with FREEDOM S1PS LOW. The anatomically shaped toe cap supports barefoot-like walking. Lightweight, breathable and metal free.

Upper	Textile
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	Nonwoven
Outsole	ETPU/Rubber (NBR)
Toecap	Nano Carbon
Category	S1 PS / SR, SC, FO, HI, HRO, CI, ESD
Size range	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
Sample weight	0.535 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



BLK



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



Nano carbon toecap

Ultralight high-tech material, metalfree with no thermal or electrical conductivity.



Breathable upper

Increased moisture and temperature management for extended wearer comfort.

**SAFETY
JOGGER**
WORKS

**HEAD-TO-TOE
PROTECTION**

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:

Assembly, Automotive, Industry, Logistics

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Textile			
	Upper: permeability to water vapor	mg/cm² /h	32.71	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	262	≥ 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm² /h	37.07	≥ 2
	Lining: water vapor coefficient	mg/cm²	297	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	ETPU/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	114	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.47	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.45	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.35	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.32	≥ 0.22
	Antistatic value	MegaOhm	42.6	0.1 - 1000
	ESD value	MegaOhm	20	0.1 - 100
	Heel energy absorption	J	33	≥ 20
Toecap	Nano Carbon			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	23.0	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.